ART I	B (To be ork, N. Y. Date	prepared by Coast	Guard Representative) 1943. Location PIER 32, NORTH RIVER			
	Name of vessel					
			Radio Call WACX			
(2)	Tame of Master		Licensee MACKAY			
(3)	*(Give under remark	AMERICAN HAWAIIAN S.S. CO.  ks complete information as to Ownership, Charter and status Crew).				
(4)	Arrival within juri Hour 0940 Date	isdiction of the United States.  11 JULY 1943. Place AMBROSE				
(5)	Last previous port	CASABIANCA, N.A. Port bound to UNKNOWN				
(6)	Nature of service	CARGO Purpose of visit LOADING				
(7)	*Remarks	44 in crew including 9 officers				
		1 Dane, 4 Swedes	, 1 Finn., 5 Filipinos, rest American			
	Number of Operators_TWO (2)					
	Names of Operators	Operators H. GOODRICH, H.J. WOOD				
(8)			. (YES ) Emergency (YES); Lifeboat (YES			
	Type	MAIN 155 B				
	Manufactured by	FTC				
	Power	300 WATTS				
	Frequency Range	375 to 500 KCs.				
	Frequency calibrated 375, 400, 425, 468, 500 KCS.					
(9)	Brief description	f scaling eperati	ons SHORTED MAIN INDUCTANC			
	THE STATE OF THE S	TIDE COMPONENTS	COIL.			
(77)	Brief description of signaling apparatus MORSE & ALDIS LAMPS.  Time sealed 2115 Eastern War Time.  I hereby certify that I have, in accordance with orders of the District Coast Guard Officer, Third Naval District, sealed the radio apparatus of the above named vessel.  The serial number (s) of the seal (s) are (is):					
	BUTTON 9486 - 9487 - 9488 - 9489 INTACT FROM					
	ARMED (YES) DEGAUSSED (YES)	a 9600 ± 190 t	C. G. Johnson			
		ots.	C.G. JOHNSON (Signature) SEA. 1/c			
		112, 1943	(Rank or Rating)			

(Rank or Rating)
Attached to Office, District
Guard Officer, Third Naval District

る。	ontinued) ansmitters:	HIGH FREQU	ENCY 156 B			
	Manufactured by	FTC				
	Power	200 WATTS	200 WATTS			
	Frequency range			× 1		
	Freq. calibrated	5515, 6230	, 8250, 11,070, 12,390,	16,560 KCS.		
(9)	Brief description of se	ealing operations SHORTED MAIN INDUCTANCE				
(8)	Transmitters: Type	EMERGENCY ET 8003				
	Manufactured by					
	Power	50 WATTS				
	Frequency range					
	Freq. calibrated	ARE 100 100 101 110 100 100				
(9)	) Brief description of sealing operations GROUNDED ANTENNA TAPE					
	Transmitters: Type LIFEBOAT 168 B					
	Manufactured by FTC					
	Power					
	Frequency range	500 KGS. ONLY				
	Freq. calibrated 500 KCS. FIXED					
		sealing operations SEALED CASE.				
RECE	CIVING APPARATUS - MAKE 8	& TYPE	FREQUENCY RANGE	STATUS OR REMARKS		
REC'R E.M. SARBENT AH 10			34 to 550 KCs.			
REC'R HALLICRAFTER S 22 R			110 to 16.7 KCS.			
REC'R E.M. SARGENT AH 5			200 to 750 KCS.			
RADIO D/F BLUDWORTH STANDARD ARROW			280 to 520 KCS.	MARINE SECURITION OF THE SECUR		
AUTC	ALARM R. M. C. A.	AR 8600 X	490 to 510 KCS.			
	Name of Vessel AR	IZONAN	Location PIER 32, N	ORTH RIVER		

Date 11 JULY, 1943 . THIRD NAVAL DISTRICT