

- (1) Name of Vessel CHERRY VALLEY Type S.S.  
Nationality AMERICAN Radio Call K F B E
- (2) Name of Master B. B. CALAWAY Licensee R.M.C.A.
- (3) Owner of Vessel A. E. DIETZE  
\*(Give under remarks complete information as to ownership, Charter and status of Officers and crew).
- (4) Arrival within jurisdiction of the United States.  
Hour 0700 Date 16 JANUARY 1943. Place CITY ISLAND
- (5) Last previous port HALIFAX, N.S. Port bound to UNKNOWN
- (6) Nature of service TANKER Purpose of visit REPAIRS
- (7) \*Remarks 74 IN CREW INCLUDING 11 OFFICERS AND 23 USN GUN CREW  
1 NOR. - REST AMERICAN
- Number of operators ONE (1)  
Names of operators T. O. SPANK
- (8) Transmitters: Main (YES ) High Freq. (YES ) Emergency (YES ) Lifeboat (YES )  
Type MAIN & EMERGENCY ET 8010-CA  
Manufactured by R.M.C.A.  
Power 200 WATTS  
Frequency range 375 to 500 KCS.  
Freq. calibrated to 375, 400, 410, 425, 468, 500 KCS.
- (9) Brief description of sealing operations SEALED POWER SWITCH IN OFF POSITION

- (10) Brief description of signaling apparatus MORSE AND ALDIS LAMPS.
- (11) Time sealed 1400 Eastern War Time.
- (12) I hereby certify that I have, in accordance with orders of the District Coast Guard Officer, Third Naval District, sealed the radio apparatus of the above named vessel.  
The serial number(s) of the seal(s) are (is):

BUTTON USC A 330520 - 329799 - 329800 - 329795 - 331761  
INTACT FROM USC

ARMED (YES )  
DEGAUSSED (YES )  
SPEED (14.5 ) KNOTS.

*J. W. Waterson*  
J. WATTERSON (Signature)  
E. M. 2/c

(Rank or Rating)  
Attached to Office, District Coast  
Guard Officer, Third Naval District.



B) (Continued)

Transmitters: HIGH FREQUENCY ET 8019  
Manufactured by R.M.C.A.  
Power 200 WATTS  
Frequency Range 3105 to 22080 KCS.  
Freq. calibrated 3105, 5520, 8280, 11040, 16560 KCS.

(9) Brief description of sealing operations SEALED POWER SUPPLY SWITCH IN OFF  
POSITION

Transmitters:  
Type RADIO TELEPHONE 24-A & 24-B  
Manufactured by WESTERN ELECTRIC  
Power 100 WATTS  
Frequency Range 2000 to 2800 KCS.  
Freq. calibrated UNKNOWN

(9) Brief description of ~~sealing~~ SEALED BOWT operations SEALED POWER SUPPLY SWITCH IN OFF  
POSITION

(8) Transmitters:  
Type LIFEBOATS (2) 168 B  
Manufactured by F.T.C.  
Power 5 WATTS  
Frequency Range 600 METERS FIXED  
Freq. calibrated 600 METERS ONLY

(9) Brief description of sealing operations SEALED CARRYING CASES

RECEIVING APPARATUS	MAKE & TYPE	FREQUENCY RANGE	STATUS OR REMARKS
REC'R	R.M.C.A. AR 8503	15 to 600 KCS.	
REC'R	R.M.C.A. AR 8505	15 to 20000 METERS	
REC'R	R.M.C.A. "B"	350 to 515 KCS.	
RADIO D/F:	R.M.C.A. AR 8703-BX	270 to 500 KCS.	
AUTO. ALARM:	R.M.C.A. AR 8600 X	585 to 615 METERS	

Name of Vessel CHERRY VALLEY Location PIER 37, NORTH RIVER

Date 16 JANUARY, 1943 THIRD NAVAL DISTRICT