

REPORT OF RADIO SEALING

- (1) Vessel S/S HOWARD Honduran Master D'Eutzemont
- (2) Owner of Vessel Empressa Honduras de Vapore
- (3) Arrival within the jurisdiction of the United States
Hour 1000 Date 7 July 1943 Place Tampa, Florida
- (4) Last previous Port Porto Cortez, Honduras
- (5) Nature of service Foreign Purpose of visit Discharge cargo

(6) Transmitters:
Type Main 155B Emergency ET:8003 Lifeboat 168B
Manufactured by Main and Lifeboat MacKay Radio Emergency R.C.A.
Power Main 300 watts, Emergency 50 watts and Lifeboat 5 watts.
Frequency Range Main and Emergency 375-500 kcs, Lifeboat 500 kcs.
Frequency to which calibrated Main 375-400-410-425-454-468-500 kcs, Emergency 375-400-425-454-468-500 kcs and Lifeboat fixed at 500 kcs.

- (7) Brief description of any signalling apparatus: Flags, flares, blinker and rockets.
- (8) Brief description of sealing operations: All switches opened and radio equipment sealed.
- (9) Remarks:

Date 7 July 1943

I hereby certify that I have, in accordance with orders of the Commander, In-shore Patrol, SEVENTH Naval District, sealed the radio apparatus of the aboved named vessel. The serial number (s) of the seal (s) used is (are):

- One button seal (no serial number) used on Main Power Switch.
- One button seal (no serial number) used on Emergency Changeover Switch.
- One button seal (no serial number) used on Lifeboat Transmitter Case.

John A. DeVito
John A. DeVito
(Signature)
Seaman 1/c USCGR.
(Rank or Rating)

Attached to: Captain of the Port Office, Tampa, Florida.

In the event the seals have not been removed by Naval Authority prior to departure, the master is authorized to remove same, only after leaving Buoy # 2, Flashing Red or when cleared by Examining vessel.

CAPTAIN OF THE PORT
Tampa, Florida
Paul V. Reese
PAUL V. REESE
By direction