



ART B) (Continued)

(8) Transmitters:

Type EMERGENCY ET 8025

Manufactured by R M C A

Power 40 Watts.

Frequency Range 375 - 500 Kc.

Freq. calibrated 375.425.454.500 Kc.

(9) Brief description of sealing operations shorted antenna inductance & sealed panel.

(8) Transmitters:

Type LIFEBOAT 168 B

Manufactured by F T C

Power 5 watts.

Frequency Range 600 Mtrs. fixed

Freq. calibrated 600 Mtrs. only

(9) Brief description of sealing operations Sealed case.

(8) Transmitters:

Type \_\_\_\_\_

Manufactured by \_\_\_\_\_

Power \_\_\_\_\_

Frequency Range \_\_\_\_\_

Freq. calibrated \_\_\_\_\_

(9) Brief description of sealing operations \_\_\_\_\_

RECEIVING APPARATUS - MAKE & TYPE	FREQUENCY RANGE	STATUS OR REMARKS
REC'R <u>R M C A</u> <u>AR 8510</u>	<u>15 - 650 Kc.</u>	
REC'R		
REC'R		
RADIO D/ <u>F T C</u> <u>106 B</u>	<u>290 - 650 Kc.</u>	
AUTO. ALARM <u>R M C A</u> <u>AR 8601</u>	<u>490 - 500 Kc.</u>	

Name of Vessel JOEL R. POINSETT Location F.A. 17

Date 19 March 1943 THIRD NAVAL DISTRICT