

PART "B" (To be prepared by Coast Guard Representative)

New York, N. Y. Date 20 August, 1942, Location F.A. 23

- (1) Name of vessel MONTANA Type S/S
 Nationality American Radio Call K F Y M
 (2) Name of Master A. Mathelsen Licensee MACKAY
 (3) Owner of vessel Texas Company

*(Give under remarks complete information as to ownership, Charter and status of officers and crew).

- (4) Arrival within the jurisdiction of the United States.
 Hour 1900 Date 19 August, 1942, Place Ambrose
 (5) Desired departure from the United States.
 Hour UNKNOWN Date UNKNOWN 1942; Place UNKNOWN
 (6) Last previous port Port Arthur, Texas
 (7) Nature of service Tanker
 Purpose of visit Discharge
 (8) Port bound to Bayonne
 (9) *Remarks 44 in crew including 10 officer.
2 British, 11 USN Gun Crew. Rest U.S.A.

Number of operators aboard One (1)

Name of each operator aboard J. C. Morrow

- (10) Transmitters: Intermediate High Freq. Low Freq.
 Type MATN 155B
 Manufactured by MACKAY
 Power 300 Watts
 Frequency range 355 to 500 Kcs.
 Frequencies calibrated to 500-468-454-425-410-400-375-355 Kcs.

- (11) Brief description of sealing operations Shorted main inductance and Sealed.

- (12) Brief description of any signalling apparatus M & A
 (13) TLE: (un) (re) (Inspected) (sealed) 1300 E. W. T.

I hereby certify that I have, in accordance with orders of the District Coast Guard Officer, Third Naval District, sealed the radio apparatus of the above named vessel.

The serial number(s) of the seals are (is):

TYDEN USC A

BUTTON USC A 285607 285606

INTACT FROM USC

- ARLID (YES)
 DEGAUSSED (YES)
 WIPED (* -)
 SPEED (17) K

Frank Weir
 (Signature) FRANK WEIR

E.M. 2C.
 Rank or rating,
 Attached to Office, District Coast
 Guard Officer, Third Naval District

(Part B Cont'd)

(10) Transmitters:

Type: HIGH FREQUENCY 156B

Manufactured by: MACKAY

Power: 200 Watts

Frequency range: 5.5 to 17 MC.

Frequencies calib rated to: 5.520-6.210-8.280-11.040-12.420-16.560- 17

(12) Brief description of sealing operations: Sealed Main inductance

Intack from Philadelphia.

(10) Transmitters:

Type: EMERGENCY 149A

Manufactured by: MACKAY

Power: 100 Watts

Frequency range: 355 to 500 Kcs.

Frequencies calibrated to: 355-375-425-468-500 Kcs.

(12) Brief description of sealing operations: Shorted antenna circuit

Sealed Panel.

(10) Transmitters:

Type: _____

Manufactured by: _____

Power: _____

Frequency range: _____

Frequencies calibrated to: _____

(12) Brief description of sealing operations: _____

RECEIVING APPARATUS * MAKE & TYPE	FREQUENCY RANGE	STATUS OR REMARKS
REC'R. MACKAY 128A	15 to 650 Kcs.	
REC'R. MACKAY 129A	1.60 to 11.2 MC.	
REC'R.		
RADIO D/F MACKAY 105R	250 to 600 Kcs.	
AUTO ALARM MACKAY 101B	500 Kcs.	

VESSEL: SS MONTANA LOCATION: F.A. 23 N.Y. Harbor

DATE: 20 August, 1942, THIRD NAVAL DISTRICT.